

Wall mounted unit

FTXG-LS/FTXG-LW



2 area intelligent eye



Energy saving during standby mode



Whisper quiet



Online controller via app



VRV for residential application

Design at its best, delivering superior efficiency and comfort

- › Remarkable blend of iconic design and engineering excellence with an elegant silver coloured or matt crystal white finish
- › Online controller (optional): control your indoor from any location with an app, via your

- local network or internet and keep an overview on your energy consumption
- › Seasonal efficiency values up to A+++ in cooling and A++ in heating

FTXG-LS/FTXG-LW



Indoor unit		FTXG	20LS	20LW	25LS	25LW	35LS	35LW	50LS	50LW
Casing	Colour		Silver	White	Silver	White	Silver	White	Silver	White
Dimensions	Unit	HeightxWidthxDepth	mm 303x998x212							
Sound power level	Cooling	dB(A)	54				59		60	
	Heating	dB(A)	56				59		60	
Sound pressure level	Cooling	High/Low/Silent operation	dB(A) 38/25/19				45/26/20		46/35/25	
	Heating	High/Low/Silent operation	40/28/19		41/28/19		45/29/20		47/35/25	
Control systems	Infrared remote control	ARC466A1								

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load


Efficiency data		FTXG + RXG	20LS + 20L	20LW + 20L	25LS + 25L	25LW + 25L	35LS + 35L	35LW + 35L	50LS + 50L	50LW + 50L
Cooling capacity	Min./Max.	kW	1.3 (1)/2.8 (1)		1.3 (1)/3.0 (1)		1.4 (1)/3.8 (1)		1.7 (1)/5.3 (1)	
Heating capacity	Min./Max.	kW	1.3 (1)/4.3 (1)		1.3 (1)/4.5 (1)		1.4 (1)/5.0 (1)		1.7 (1)/6.5 (1)	
Power input	Cooling	Min./Nom./Max.	kW 0.320 (1)/0.501 (1)/0.760 (1)		0.320 (1)/0.523 (1)/0.820 (1)		0.350 (1)/0.882 (1)/1.190 (1)		0.370 (1)/1.360 (1)/1.880 (1)	
	Heating	Min./Nom./Max.	kW 0.310 (1)/0.500 (1)/1.120 (1)		0.310 (1)/0.769 (1)/1.320 (1)		0.320 (1)/0.985 (1)/1.490 (1)		0.310 (1)/1.589 (1)/2.490 (1)	
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A+++				A++			
		Pdesign	kW 2.30		2.40		3.50		4.80	
		SEER	8.52		8.50		7.00		6.70	
	Heating (Average climate)	Energy efficiency class	A++				A+			
		Pdesign	kW 2.10		2.70		3.00		4.60	
		SCOP/A	4.60		4.60		4.24		4.24	
Nominal efficiency	EER	Annual energy consumption	kWh 639		821		913		1,519	
		EER	4.59 (2)		3.97 (2)		3.53 (2)			
		COP	5.00 (2)		4.42 (2)		4.06 (2)		3.65 (2)	
Annual energy consumption	kWh	250.5		261.5		441		680		

(1) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load (2) EER/COP according to Eurovent 2012, for use outside EU only

Outdoor unit		RXG	20L	25L	35L	50L
Dimensions	Unit	HeightxWidthxDepth	mm 550x765x285			735x825x300
Sound power level	Cooling	dB(A)	61			63
	Heating	dB(A)	62			63
Sound pressure level	Cooling	High/Silent operation	dB(A) 46/43			48/44
	Heating	High/Silent operation	47/44			48/44
Operation range	Cooling	Ambient	Min.-Max. °CDB -10 ~-46			
	Heating	Ambient	Min.-Max. °CWB -15 ~-18			
Refrigerant	Type/Charge/GWP	kg/TCO _{eq}	R-410A/1.05/2.2/2,087.5			R-410A/1.6/3.3/2,087.5
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

ECPEN16-020

01/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.